

| TX Design # | MVA Rating @ 65 Deg. C | HV Rating (volts) | HV Taps (volts) | LV Rating (volts) | LV Taps | % Imped. HV-LV | LTC | 1 or 3 Phase | High Voltage CT | | | Low Voltage CT | | | Neutral CT | | |
|-------------|------------------------|-------------------|---|-------------------|---------|------------------|-----|--------------|-----------------|-----------------|---------------|----------------|-----------------|---------------|------------|-----------------|---------------|
| | | | | | | | | | Ratio | Accuracy Rating | Rating Factor | Ratio | Accuracy Rating | Rating Factor | Ratio | Accuracy Rating | Rating Factor |
| 1 * | 11.2/14 | 44,000 | 47,000 46,000 45,000 44,000 43,000 42,000 | 13,090Y/7,560 | None | 7.3% @ 11.2 MVA | No | 3 Phase | 600/5 | C400 | 1.0 | N/A | N/A | N/A | 1200/5 | C400 | 1.0 |
| 2 | (Deleted) | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 3 | 3.733 | 44,000 | 46,000 45,000 44,000 43,000 42,000 | 7,560 X 2,520 | None | 7.3% @ 3.733 MVA | No | 1 Phase | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| 4 | (Deleted) | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 5 | 13.4/18/22.4 | 105,750 | 105,750 103,500 101,250 99,000 96,750 94,500 | 13,800Y/7,960 | None | 9.5% @ 13.4 MVA | No | 3 Phase | 600/5 | C800 | 1.0 | 1200/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |
| 6 | 22.4/30/37.33 | 105,750 | 105,750 103,500 101,250 99,000 96,750 94,500 | 13,090Y/7,560 | None | 13.2% @ 22.4 MVA | Yes | 3 Phase | 600/5 | C800 | 1.0 | 2000/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |
| 7 | 22.4/30/37.33 | 103,500 | 103,500 101,250 99,000 96,750 94,500 | 24,940Y/14,400 | None | 13.2% @ 22.4 MVA | Yes | 3 Phase | 600/5 | C800 | 1.0 | 1200/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |
| 8 | 33.6/44.8/56 | 103,500 | 103,500 101,250 99,000 96,750 94,500 | 24,940Y/14,400 | None | 13.2% @ 33.6 MVA | Yes | 3 Phase | 600/5 | C800 | 1.0 | 2000/5 | C400 | 1.0 | 1200/5 | C400 | 1.0 |
| 9 | 13.4/18/22.4 | 105,750 | 105,750 103,500 101,250 99,000 96,750 94,500 | 13,090Y/7,560 | None | 9.5% @ 13.4 MVA | No | 3 Phase | 600/5 | C800 | 1.0 | 1200/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |
| 10 | 13.4/18/22.4 | 103,500 | 103,500 101,250 99,000 96,750 94,500 | 24,940Y/14,400 | None | 9.5% @ 13.4 MVA | No | 3 Phase | 600/5 | C800 | 1.0 | 1200/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |
| 11 | 22.4/30/37.33 | 105,750 | 105,750 103,500 101,250 99,000 96,750 94,500 | 13,090Y/7,560 | None | 13.2% @ 22.4 MVA | No | 3 Phase | 600/5 | C800 | 1.0 | 2000/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |
| 12 | 22.4/30/37.33 | 103,500 | 103,500 101,250 99,000 96,750 94,500 | 24,940Y/14,400 | None | 13.2% @ 22.4 MVA | No | 3 Phase | 600/5 | C800 | 1.0 | 1200/5 | C400 | 1.5 | 1200/5 | C400 | 1.0 |